

# XD140



# XD140

Vibratory Roller

XD140 is suitable for compaction of soil and asphalt pavement in narrow areas such as sidewalks, parking lots and residential roads, it can also be used for compacting thin stable soil layering, which is an ideal compaction equipment for asphalt surface laminating in municipal maintenance and high-speed pipe maintenance.


## Performance and characteristics

- 60Hz high frequency vibration, 920mm large diameter roller, effectively improve the quality of compaction.
- Large-capacity water tank, interval controlled sprinkling for prolonged operation.
- Two-wheel drive, large displacement and high driving torque, superior climbing ability.
- Drum and articulated frame are maintenance-free during the whole life cycle.
- Sliding operation mechanism for more convenient edge compaction.

## Main dimensions

Unit: mm

Model	L	L1	W	W1	H	H1	H2	S	D
XD140	2910	1950	1515	1380	1980	2720	350	16	920



## Main specifications

Item	Content	Unit	XD140
<b>Weights</b>	Operating weight	kg	4300
	Maximum operating weight	kg	4400
	Front axle weight	kg	2100
	Rear axle weight	kg	2200
	Static linear load	N/cm	152/159
<b>Maneuverability</b>	Operating speed	km/h	0-12
	Gradeability	%	30
	Minimum turning radius(outer)	mm	4100
	Minimum ground clearance	mm	350
	Wheel base	mm	1950
	Steering angle	°	±32
	Oscillation angle	°	±8
<b>Compaction parameters</b>	Vibration frequency	Hz	53/60
	Nominal amplitude	mm	0.5
	Excitation force	kN	42/53
	Drum diameter	mm	920
	Drum width	mm	1380
<b>Engine</b>	Model	-	V2403
	Emission		EU Stage V/EPA TIER4f
	Rated power	KW	33.6
	Rated speed	r/min	2400
<b>Capacities</b>	Fuel tank	L	55
	Water tank	L	280